

Installation Instructions

1968-1972 CHEVELLE TUBULAR LOWER CONTROL ARMS

*Please read these instructions completely **BEFORE** starting your installation!*

Your *HEIDTS* Hot Rod Shop 1968-1972 Chevelle Tubular Lower Control Arms contains the following items:

- 2) Tubular Lower Control Arms
- 1) Installation Hardware Kit

Begin your installation by jacking up the front of the car and supporting it on sturdy jack stands. Remove the front wheels. Raise one lower control arm with a floor jack. Remove the shock absorber. Using an internal spring compressor, compress the coil spring until it is loose in the lower control arm spring pocket. Remove the cotter pin and castle nut from the lower ball joint and remove the ball joint from the spindle. Swing the spindle aside, and swing the lower control arm down until the spring can be removed from the control arm. Unbolt and remove the lower arm. Remove the spring from the frame. Install the new *HEIDTS* Tubular Lower Control Arm into the frame using the supplied bushing bolts and nuts. Insert the spring up into the frame, and swing the control arm up to the spring. Insert the ball joint into the spindle and install the castle nut onto the ball joint stud and tighten down the castle nut and insert the cotter pin. Remove the spring compressor and reinstall the shock absorber. Install the urethane snubber into the tapped hole in the control arm tube. Slowly release the jack, and complete the installation on the other side of the car. Be certain to grease the ball joints upon completion. Place the wheels back on, and place the car back on the ground. You will need to check the front suspension alignment, as the new control arms have new ball joints and may be seated different than the old ones.

